

PRODUCT SPECIFICATION

Customer	
Project	
Part No.	Z35017-P40-总成 3
Remarks	<input type="checkbox"/> APPOVAL FOR SPECIFICATION ONLY <input checked="" type="checkbox"/> APPOVAL FOR SPECIFICATION AND SAMPLE

CUSTOMER			ZHUNYIKEJI		
Approved	Checked	Prepared	Approved	Checked	Prepared
By	By	By	By	By	By
				Shi Jin	Yang Zifeng

Revision Record

Rev. No.	Date	Description
V1.0	2023-04-06	Preliminary Specification Release.

Contents

1. General Specifications.....	3
2. Interface Definition Description.....	4
3. Mechanical Drawing.....	5
4. Electrical Specifications.....	7
5. Delivery Inspection.....	11
6. Reliability Test.....	13
7. Precautions.....	14
8. Packing and Storage.....	16

1. General Specifications

No.	Item	Specification	Unit
1	Display Size (Diagonal)	3.5	inch
2	Display Resolution	320(H) × RGB × 480 (V)	pixels
3	Pixel Pitch	153(H) × 153 (V)	um
4	LCM Outline Dimension (Without FPC)	53.76 (W) × 82.39 (H) × 2.23 (T)	mm
5	CTP Outline Dimension (Without FPC)	55.46 (W) × 83.94 (H) × 4.25 (T)	mm
6	LCD Outline Dimension	51.96 (W) × 80.22 (H) × 0.8 (T)	mm
7	LCD Active Area	48.96 (W) × 73.44 (H)	mm
8	View Direction (Gray Inversion)	FULL VIEW	-
9	Driver IC	ILI9488	-
10	Pixel Arrangement	RGB-Stripe	-
11	Display Mode	Normal Black	-
12	Pixel driving Element	a-Si TFT	-
13	LCD Transmittance	Typ.: 4.05% Min:3.45%	-
14	LCD Contrast Ratio	Typ.: 1000 Min:800	-
15	FPC Version	Z35017-P40 V3	-
16	Interface	MCU18BIT/SPI+ 18BIT RGB	-
17	Operating Temperature	-20°C~ 70°C	-
18	Storage Temperature	-30°C~ 80°C	-
19	Backlight Arrangement	LED/3 Series 2 Parallel (6 lights in total)	-
20	Luminance	220	nit
21	Weight	0.035	kg

2. Interface Definition Description

2.1 LCM PIN

PIN NO.	PIN DEF.	FUNCTION DESC.
1	GND	Ground
2-3	VCI	Power supply for analog circuit
4	IM0	Interface mode select PIN
5	IM1	Interface mode select PIN
6	IM2	Interface mode select PIN
7	RESET	Reset pin
8	VSYNC	Vertical synchronizing input signal for RGB interface
9	HSYNC	Horizontal synchronizing input signal for RGB interface
10	PCLK	Dot clock signal for RGB interface operation
11	DE	Data enable signal for RGB interface operation
12-29	DB17-DB0	DATA BUS
30	GND	Ground
31	DOUT	SPI interface output pin
32	DIN_SDA	SPI interface input pin
33	RDX	Read enable in 8080 MCU parallel interface
34	WRX_SCL	Write enable in MCU parallel interface In SPI mode, this pin is used as SCL
35	DCX	Display data/command selection (RS) pin in MCU interface
36	CSX	Chip selection pin
37	LEDA	LED Anode
38	LEDK1	LED Cathode
39	LEDK2	LED Cathode
40	GND	Ground


RESET voltage should be consistent with VDDI voltage, or there probably is black screen fault when power on.

2.1 TP PIN

PIN NO.	PIN DEF.	FUNCTION DESC.
1	TP-VDD(3.3V)	TP POWER SUPPLY(3.3V)
3	TP-GND	Ground
4	TP-SCL(3.3V)	TP I2C clock (SCL) clock (SCLK)(3.3V)
4	TP-SDA(3.3V)	TP I2C data (SDA) data input (MOSI)(3.3V)
5	TP-INT(3.3V)	TP Interrupt PIN(3.3V)
6	TP-RESET(3.3V)	TP Reset PIN(3.3V)

3. Mechanical Drawing

3.1 LCM



3.2 CTP

正面图

侧面图

背面图

技术要求	
1	产品结构类型 Structure: G1 ass+P1 m+P1 Im
2	COVER LENS 钢化类型 Strengthening: 超薄子 1.100 化学钢化
3	COVER LENS 表面硬度 Surface Hardness: >=6H
4	无油雾穿透光率 Transmission: >=83%
5	工作温度 Operation temperature: -20°C ~ -70°C(50%RH)
6	储存温度 Storage temperature: -30°C ~ 80°C(50%RH)
7	是否进行物理碰撞测试? <input type="checkbox"/> 是 <input checked="" type="checkbox"/> 否
8	物理碰撞测试是否喷水测试? <input type="checkbox"/> 是 <input checked="" type="checkbox"/> 否
9	是否进行功能性能子测试? <input type="checkbox"/> 是 <input checked="" type="checkbox"/> 否
10	功能性与底座台位是否匹配? <input type="checkbox"/> 是 <input checked="" type="checkbox"/> 否
11	表面涂油要求? 202 漆一体效果? <input type="checkbox"/> 是 <input checked="" type="checkbox"/> 否

技术要求

所有产品物料必须满足ROHS和REACH环保要求

All materials comply with ROHS & REACH requirements

接口类型 Interface: <input checked="" type="checkbox"/> IIC <input type="checkbox"/> I2C <input type="checkbox"/> USB <input type="checkbox"/> UART
触控代码号 Touch IC: <input checked="" type="checkbox"/> FT9111 <input type="checkbox"/> 通道数 Channels: <input checked="" type="checkbox"/> 7x <input type="checkbox"/> 8x
供电电压 VDD: <input checked="" type="checkbox"/> 3.3V <input type="checkbox"/> 5V <input type="checkbox"/> 3.3V <input type="checkbox"/> 1.8V
供电电压 VIO: <input type="checkbox"/> 3.3V <input type="checkbox"/> 1.8V
备注: SIMA, SCL 主板上是否有上拉电阻

堆叠图

GLASS: 超薄子 T=1.1
TOP OCA T=0.125
TOP FILM T=0.125
BOT OCA T=0.05
BOT FILM T=0.125

CTP Pin description
1 TP-100V(3.3V)
2 TP-GND
3 TP-SCL
4 TP-SDA
5 TP-INT
6 TP-RESET

1 GND	2 VCI	3 VCI	4 IM0	5 IM1	6 IM2	7 RESET	8 VSYNS	9 HSYSNS	10 PCLK	11 DE	12 DB17	13 DB16	14 DB15	15 DB14	16 DB13	17 DB12	18 DB11	19 DB10	20 DB9	21 DB8	22 DB7	23 DB6	24 DB5	25 DB4	26 DB3	27 DB2	28 DB1	29 DB0	30 GND	31 DOUT	32 DIN_SDA	33 RDX	34 WRX_SCL	35 DOX	36 CSX	37 LEDA	38 LEDK1	39 LEDK2	40 GND
-------	-------	-------	-------	-------	-------	---------	---------	----------	---------	-------	---------	---------	---------	---------	---------	---------	---------	---------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	---------	------------	--------	------------	--------	--------	---------	----------	----------	--------

UNIT: mm	Drawn By: 石进	Checked By:	Approved By:
DESCRIPTION: ZC			
PART NO.: Z3501-T-P40-总成3			
DRAWING NO.			

4. Electrical Specifications

4.1. LCD Optical Characteristics

Item	Symbol	Conditions	Specification			Unit	Note	
			Min.	Typ.	Max.			
Transmittance (With PL)	T(%)	Viewing normal angle $x = y = 0$	3.45	4.05	-	%	-	
Contrast Ratio	CR		800	1000	-	-	-	
Response Time	TR+TF		-	25	35	ms	-	
Viewing Angle	Hor.	Θ_{x+}	CR \geq 10 at 25°C	80	85	-	deg.	-
		Θ_{x-}		80	85	-		
	Ver.	Θ_{y+}		80	85	-		
		Θ_{y-}		80	85	-		

4.2. Electrical Specifications

Item	Symbol	Specification			Unit
		Min.	Typ.	Max.	
Power For Analog Circuit	AVDD	-	-	-	V
TFT Gate On Voltage	VGH	10	12	14	V
TFT Gate Off Voltage	VGL	-14	-12	-10	V
TFT Common Electrode Voltage	Vcom	-2	-	0	V

4.3. Typical Operating Conditions

Item	Symbol	Min.	Typ.	Max.	Unit
Analog Supply Voltage	VCI	2.5	2.8	3.3	V
I/O Supply Voltage	1.8V	1.65	1.8	3.3	V
Input High Voltage	VIH	$0.7 \times VCI$	-	VCI	V
Input Low Voltage	VIL	-0.3	-	$0.3 \times VCI$	V

Output High Voltage	VOH	$0.8 \times V_{CI}$	-	VCI	V
Output Low Voltage	VOL	0	-	$0.2 \times V_{CI}$	V

4.4. Backlight Circuit Specifications

Item	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Current	I _B	-	40	-	mA	-
Voltage	V _f	8.1	9	9.3	V	-
LCM Uniformity	-	80	-	-	%	If=40mA
Life Time	-	30000	-	-	Hr.	
Power Consumption	PBL	-	360	-	mW	
LCM Chromaticity Coordinate	Red	R _x	0.611	0.626	0.641	Average the brightness EV at 9 points, Optical Instrument BM-7
		R _y	0.325	0.340	0.355	
	Green	G _x	0.294	0.309	0.324	
		G _y	0.589	0.604	0.619	
	Blue	B _x	0.127	0.142	0.157	
		B _y	0.035	0.050	0.065	
	White	W _x	0.272	0.287	0.302	
		W _y	0.304	0.319	0.334	


4.5. LCD Power Consumption

Mode	Symbol	Typ.	Max.	Unit
Normal Mode	VCI+1.8V	-	-	mA
Test Condition: VCI=3.3V.				
Interface Drive Type: row flipping or column flipping.				
IPS Type LCD Panel => All Black Pattern.				
TN Type LCD Panel => All White Pattern.				
Temperature: 25°C.				
Mode	Symbol	Typ.	Max.	Unit

Sleep Mode	VCI+1.8V	-	-	μA
Test Condition: VCI=3.3V.				
DC/DC converter is enabled. Internal oscillator is started and panel scanning is started.				
Except for the IC internal crystal oscillator and panel scanning, other functions are suspended.				
Temperature: 25°C.				


4.6. Measuring System

4.6.1. LCM Viewing Angle



Viewing angle is the angle at which the contrast ratio is greater than 10. The angles are determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to the LCD surface.

4.6.2. Response Time



Response time is the time required for the display to transition from white to black (Rising time, T_r) and from black to white (Falling time, T_f) for additional information.

4.6.3. Contrast Ratio (CR)

Contrast Ratio (CR) is defined mathematically as:

$$\text{Contrast Ratio} = \frac{\text{Surface Luminance with all white pixels}}{\text{Surface Luminance with all black pixels}}$$


Surface luminance is the center point across the LCD surface 500mm from the surface with all pixels displaying white.

4.7. Power On / Power Off

4.7.1. Power On/Off

Case 1 – RESX Line is Held High or Unstable by Host at Power ON


If the RESX line is held High or unstable by the host during Power On, then Hardware Reset must be applied after both VCI and IOVCC have been applied. Otherwise, the correct functionality is not guaranteed. There is no timing restriction upon this hardware reset.



Note: Unless otherwise specified, timings herein show the cross point at 50% of the signal power level.

Case 2 – RESX Line is Held Low by Host at Power ON

If the RESX line is held Low (and stable) by the host during Power On, then the RESX must be held low for a minimum of 10µsec after both VCI and IOVCC have been applied.




5. Delivery Inspection

5.1. Quality Inspection Environmental Conditions

5.1.1. Viewing distance: the normal viewing distance between the screen and the inspector is $30\pm 5\text{cm}$; Inspection Angle: $90^\circ\pm 45^\circ$ (90° indicates that the inspector's perspective is perpendicular to the product to be inspected).

5.1.2. Visual inspection illumination: $1000\pm 200\text{LUX}$; Electrical inspection illumination: $200\pm 100\text{LUX}$; Ambient temperature $25\pm 5^\circ\text{C}$, ambient humidity $55\pm 15\%\text{RH}$.



5.2. Quality Inspection Standard

No.	Defect	Standard		Defect Grade	Result
1	Spot Defect (including bright spot / color spot / bubble / dark spot, etc.)	< 7 inches	$\Phi \leq 0.10\text{mm}$	Ignore	OK
			$0.10\text{mm} < \Phi \leq 0.20\text{mm}$	Minor Defect	OK
			$\text{DS} \geq 10\text{mm}$		
		$\cong 7$ inches	$\Phi > 0.20\text{mm}$	Serious Defect	NG
			$\Phi \leq 0.15\text{mm}$	Ignore	OK
			$0.15\text{mm} < \Phi \leq 0.25\text{mm}$	Minor Defect	OK
		$\text{DS} \geq 10\text{mm}$			
		$\Phi > 0.25\text{mm}$	Serious Defect	NG	
Φ : defect diameter. DS: spacing.					
2	Linear Defect (scratches,	< 7 inches	$W \leq 0.02\text{mm}$, L: unlimited	Ignore	OK

	filaments, etc.)		0.02mm < W ≤ 0.03mm		Minor Defect	OK
			L ≤ 5mm			
			W > 0.03mm		Serious Defect	NG
			≧ 7 inches	W ≤ 0.03mm		
		L: unlimited				
		0.03mm < W ≤ 0.05mm		Minor Defect	OK	
L ≤ 5mm						
		W > 0.05mm		Serious Defect	NG	
W: defect width. L: defect length. DS: spacing.						
3	Polarizer Bubble	Display Area	Judge by Spot Defect			
		Black Edge Area	The distance from the edge of the display area is greater than 0.5mm.		Minor defect	OK
			The distance from the edge of the display area is less than 0.5mm.			
4	Polarizer Bump (Mark)	Display Area / Black Edge Area	Invisible when the touch screen or cover plate is assembled.		Minor Defect	OK
5	Color and Luminance	Item	Method	Instrument	Median	Tolerance Range
		Color	x, y Color Coordinate	Optical Instrument BM-7	According to the actual test on the sample confirmed by the customer.	± 0.04
		Luminance	Average the brightness EV at 9 points	Optical Instrument BM-7	According to the actual test on the sample confirmed by the customer.	± 20%
6	Other Standards	Subject to the negotiation by both parties.				

7	Warranty Period	One year after sale.
8	Guarantee	ROHS、REACH
9	Websites	Official: https://en.zhunyiikeji.com/ Goble Resources: https://zhunyi.manufacturer.globalsources.com/ Alibaba: https://zhunyiikeji.en.alibaba.com/ 1688: https://shop9641057ru80o3.1688.com/

6. Reliability Test

Item	Condition	Result Determination
High-Temperature Storage	80°C 120H	After the test, leave the LCD samples indoors at normal temperature and humidity for 2H for function and appearance inspection. The sample should meet the requirements on electrical performance, but be free from the following defects: 1. Air bubble in the module, 2. No display, 3. Glass crack.
Low-Temperature Storage	-30°C 120H	
High-Temperature Operation	70°C 120H	
Low-Temperature Operation	-20°C 120H	
High-Temperature and High-Humidity	60°C 90%RH 120H	
Thermal Cycling Test	-30°C/0.5H ~ +80°C/0.5H 100 cycles in total	
Vibration Test	Frequency: 10Hz ~ 55Hz ~ 10Hz Amplitude: 0.75mm Cycle once a minute, 30 cycles in total (Packing Condition)	
ESD Test	±4kV Human Body Mode 150pF/330Ω ±8kV Air Mode 150pF/330Ω	

Note:

- 1) Each module under test can only be used for one of the test items.
- 2) The quantity of samples for each test item is 2.
- 3) **Fault Judgment Criterion: Basic Specifications, Electrical Specifications, Mechanical Specifications, Optical Specifications.**

7. Precautions

- 7.1. The display screen consists of glass and polarizer. Since the glass is fragile, the user must pay special attention to the edge area, and protect it from falling, vibration, or mechanical impact.
- 7.2. If the display screen is damaged and the liquid crystal material leaks, be sure not to get any in the mouth. If the liquid crystal material contacts the skin or clothes, flush off with soap and water.
- 7.3. Do not apply excessive force to the display screen or the joint part, or the color will change. Do not touch the display screen with bare hands, which will stain the display area and degraded insulation between terminals (some of the appearance is determined by the polarizer).
- 7.4. The polarizer covering the display panel of the LCD module is soft and easy to be scratched, be sure to handle carefully. Do not touch, impact, press, or rub the exposed polarizers with anything harder than an HB pencil lead (e.g.: glass, tweezers, etc.). Do not place or attach anything onto the display area to avoid leaving marks. The condensed material on the surface or terminals due to cold will damage or stain the polarizer. After the test in low temperature environment, the product must be warmed up in a container before put into the room temperature environment.
- 7.5. If the display panel is stained, blow warm air onto the surface and gently wipe it with a soft and dry cloth. If it is seriously contaminated, wipe it with a wet cloth dipped in one of the following solvents:
 - glycerol
 - ethyl AlcoholDo not scrub, and avoid damaging the display panel.
- 7.6. Solvents other than those mentioned above may damage the polarizer. In particular, never use any of the following solvents:
 - water
 - ketone
 - areneWipe off saliva or water drop immediately, the contact with water over a long period of time may cause deformation or color fading. Avoid contact with oil or grease.
- 7.7. Special note: minimize electrode corrosion. Because electrode corrosion can be accelerated by water droplets, condensation of humidity, or electrification in a high humidity environment.
- 7.8. Assemble the LCD Module by the mounting holes. Make sure the LCD module make sure there is no bending, distortion, or deformation. Do not forcibly pull or bend the transmission wire or the backlight wire.

- 7.9. Do not disassemble the LCD module.
- 7.10. NC terminal should be disconnected. Do not connect any device.
- 7.11. If the logic circuit power supply is off, do not send the input signal.
- 7.12. Since the LCD module is integrated with CMOS, pay special attention to the modules. To prevent electrostatic damage, be careful to maintain a suitable work environment.
 - Make sure the module has the same potential as the human body before take the LCD module out of the packing box for assembly. The reliable grounding is necessary during module processing.
 - The required tool, such as the electric soldering iron, must be reliably grounded. Make sure it is connected to AC power supply, and no electric leakage. When fixing the module with electric screwdriver, it must be grounded, to reduce the electromagnetic wave generated by the electric commutator spark as much as possible.
 - Do not assemble or operate under dry condition to reduce the static electricity. To reduce static electricity, the workplace must not be too dry. The recommended relative humidity is 50 - 60%.
Keep your work clothes and work table grounded as much as possible
 - The LCD module is coated with a film to protect the display surface. Be careful when peeling off the film to reduce the generated static electricity.
- 7.13. Since the LCD module has high precision assembly and regulation, try to avoid excessive impact on the module or making any changes:
 - Do not change the shape of the tab on the metal frame.
 - Do not drill any extra hole, modify the shape, or change the position of component on the printed circuit board.
 - Do not change or damage the pattern on the printed circuit board.
 - Never modify the zebra strip (conductive rubber) or heat seal connector.
 - Do not make any change with the electric soldering iron except for the joint.
 - Do not throw, bend or twist.

8. Packing and Storage


8.1. Packing Method

Step 1



Take 1pcs of the product, put it into a anti-static bag.

Step 2



Take 2 bags of product to place into the carton, make sure they are surface to surface. Put a piece of EPE pad between the carton and the separator to protect the products.

Step 3



Put the products into cartons one by one, each carton contains 60 pieces of products.

Step 4



The cartons should be taped and shipped with labels.

8.2. Storage Method


Store in an ambient temperature of $23\pm 5^{\circ}\text{C}$, and in a relative humidity of $60\pm 15\%$. The storage period should not exceed 12 months. Do not expose to the sun for a long period of time.

8.2.1. Store in clean environment, free from dust, active gas, or solvent.





8.2.2. Store in anti-static environment.

8.3. Nomenclature



PART NO: Z 3 5 0 1 7 - P 4 0 - XXXX - 总成 3



8.4. Label

Shenzhen Zhunyi Technology Co., Ltd.		
Product:	Display Screen	LEVEL:3
Spec.:		
P/N:		
Lot:	  	
D/C		
Qty.:		
Supplier Code:		
PO		
R/K		
Version: A		
	XXXXXXXX, YYYY-0000000000000000, KKKK, WWWW, AAAAA.	

8.5. Product appearance identification

Item	Description	Production QR Code Position Display
 QR Code Content	www.zhunyi.com 13823705290	
Printing Code appearance and content	Z35017-P40-总成 3 YYMMDD+Time+5 digits serial number	
<ol style="list-style-type: none"> Customer have detail position and direction requirements(Refer to right picture for details) . Control content,format,position of the QR Code strictly. 		