

# ZHUNYI PRODUCT LIST—20250325

No.	Display Size (inch)	Display Resolution	View Direction	Active Area (mm)	LCM Outline Dimension (mm)	Thickness (mm)	Interface	Operating Temperature	Storage Temperature	Shape	Remarks	Remarks
1	0.71	160*160	IPS	18.00*18.00	20.12*22.30	1.90	SPI	-20°C ~ 70°C	-30°C ~ 80°C	round	-	
2	1.3"	240*240	IPS	23.40*23.40	26.17*29.22	1.50	SPI	-20°C ~ 70°C	-30°C ~ 80°C	square	-	
3	1.28"/1.3"	240*240	IPS	23.40*23.40	35.60*38.10	1.50	SPI	-20°C ~ 70°C	-30°C ~ 80°C	round	-	highly recommended
4	1.46"	360*360	IPS	36.94*36.94	39.30*40.96	1.60	SPI	-20°C ~ 70°C	-30°C ~ 80°C	round	-	
5	1.54"	240*240	IPS	27.72*27.72	31.50*35.00	1.90	MCU/SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	square	-	
6	1.6"	400*400	IPS	39.84*39.84	42.14*44.34	1.94	QSPI	-20°C ~ 70°C	-30°C ~ 80°C	round	-	highly recommended
7	2.0"	240*320	IPS	30.60*40.80	37.68*51.32	2.30	MCU/SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	4:3	-	
8	2.1"	480*480	IPS	53.28*53.28	56.18*59.71	2.30	RGB+SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	round	-	
9	2.4"	240*320	TN/IPS	36.72*48.76	40.52*57.00	2.40	MCU/SPI/RGB/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	4:3	-	highly recommended
10	2.73"	320*320	IPS	48.96*48.96	53.54*58.74	2.54	MCU/RGB/SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	square	-	highly recommended
11	2.8"	480*480	IPS	70.12*70.12	73.03*76.48	2.30	RGB+SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	round	-	
12	2.83"incell	400*800	IPS	32.10*64.20	34.40*69.35	2.10	QSPI/RGB/MIPI	-20°C ~ 80°C	-30°C ~ 80°C	2:1	Private glass mold	highly recommended
13	3.0"	480*854	IPS	37.44*66.61	42.70*74.70	2.45	RGB+SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	16:9	Private glass mold	highly recommended
14	3.4"	480*480	IPS	60.48*60.48	65.72*69.64	2.45	RGB+SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	square	-	highly recommended
15	3.4"	800*800	IPS	87.60*87.60	94.90*96.95	2.30	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	round	-	
16	3.4"incell	540*960	IPS	42.00*74.72	44.30*79.87	2.10	QSPI/RGB/MIPI	-20°C ~ 80°C	-30°C ~ 80°C	16:9	Private glass mold	highly recommended
17	3.5"	640*960	IPS	49.92*74.88	54.22*83.58	3.54	MIPI	-30°C ~ 70°C	-30°C ~ 80°C	16:9	-	
18	3.5"	640*480	IPS	70.08*52.56	74.50*62.40	2.45	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	4:3	-	
19	3.92"	320*320	IPS	71.14*69.82	74.86*76.73	2.17	MCU/RGB/SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	square	-	
20	3.95"	480*480	IPS	68.00*68.00	74.828*78.978	2.15	RGB+SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	square	-	
21	3.95"	720*720	IPS	71.93*71.93	74.83*78.98	2.15	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	square	-	
22	3.97"	480*800	IPS	51.84*86.40	57.14*96.85	2.15	RGB+SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	4:3	-	highly recommended
23	4.0"	720*720	IPS	101.52*101.52	105.6*109.87	2.22	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	round	-	
24	4.1"incell	480*1080	IPS	42.00*94.50	44.10*99.45	2.06	MIPI	-20°C ~ 80°C	-30°C ~ 80°C	rectangle	Private glass mold	highly recommended
25	4.3"	480*272	IPS	95.04*53.86	105.46*67.16	2.75	RGB	-30°C ~ 70°C	-30°C ~ 80°C	9:16	-	
26	4.6"	320*960	IPS	36.708*110.304	41.568*118.8	2.50	MCU/RGB/MIPI	-30°C ~ 85°C	-30°C ~ 85°C	Bar	-	
27	5.0"	480*854	IPS	61.33*109.65	66.40*120.05	2.25	RGB+SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	16:9	-	
28	5.0"	720*1280	IPS	62.10*110.40	64.40*115.45	2.10	MIPI	-20°C ~ 80°C	-30°C ~ 80°C	16:9	-	highly recommended
29	5.0"	600*600	IPS	89.28*89.28	95.08*99.5	2.70	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	square	-	
30	5.5"	720*1280	IPS	68.04*120.96	71.00*130.20	1.65	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	16:9	-	highly recommended
31	6.0"	720*1480	IPS	66.74*137.19	70.80*145.50	2.25	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	18:9	-	highly recommended
32	6.5"	540*1170/720*1560	IPS									highly recommended
33	6.75"/6.86"	480*1280	IPS	60.19*160.51	65.78*171.75	2.60	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	Bar	-	

# ZHUNYI PRODUCT LIST—20250325

No.	Display Size (inch)	Display Resolution	View Direction	Active Area (mm)	LCM Outline Dimension (mm)	Thickness (mm)	Interface	Operating Temperature	Storage Temperature	Shape	Remarks	Remarks
34	6.75"/6.9"	720*1440	IPS	78.02*156.04	81.71*163.34	2.35	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	18:9	-	highly recommended
35	6.9"	280*1424	IPS	33.6*170.88	38.2*181.47	3.45	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	Bar	-	
36	6.95"/incell	600*1024	IPS	89.28*152.37	95.00*163.20	2.55	MIPI	-10°C ~ 50°C	-20°C ~ 60°C	16:9	-	highly recommended
37	7.0"	1024*600	IPS/TN	154.21*85.92	163.70*96.90	2.55	LVDS/RGB/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	Landscape	-	
38	8.0"/incell	800*1280	IPS	107.64*172.22	114.66*184.16	2.65	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	16:9	-	highly recommended
39	8.9"/9.0"	800*1280	IPS	119.28*190.85	125.48*202.90	2.60	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	16:9	Private glass mold	highly recommended
40	10.1"	1024*600	IPS	222.72*125.28	235.1*143.2	4.30	LVDS	-20°C ~ 70°C	-30°C ~ 80°C	Landscape	-	
41	10.1"/incell	800*1280/1200*1920	IPS	135.36*216.58	143.00*228.50	2.60	MIPI	-10°C ~ 60°C	-20°C ~ 70°C	16:9	-	
42	10.1"	1280*800/1920*1200	IPS	216.96*135.60	224.02*147.76	2.60	LVDS	-20°C ~ 70°C	-30°C ~ 80°C	9:16	-	
43	10.25"/incell	1920*720/720*1920	IPS	243.65*91.37	265.2*109.8	6.50	LVDS double 8	-20°C ~ 70°C	-30°C ~ 80°C	Landscape	-	highly recommended
44	12.1"	1280*800	IPS	261.12*163.2	275.85*179.15	5.60	LVDS	-20°C ~ 70°C	-30°C ~ 80°C	Landscape	-	
45	12.3"	1920*720	IPS	292.03*109.51	305.34*122.41	2.96	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	Landscape	-	highly recommended
46	13.3"	1920*1080	IPS	293.76*165.24	300.32*177.42	2.60	EDP/LVDS=In-line/back fold is OK	0°C ~ 50°C	-20°C ~ 60°C	16:9		
47	15.6"	1920*1080	IPS	344.16*193.59	350.66*214.79	2.80	EDP=In-line/back fold is OK	0°C ~ 50°C	-20°C ~ 60°C	Landscape	-	highly recommended

Shared Product
Z07101
Z13001
Z13008/Z13011
Z14601
Z15002
Z16004
Z20011
Z21009
Z24009/Z24017/Z24023
Z27002
Z28019
Z30010/Z30032/Z30054
Z34011/Z34012
Z34009
Z35026/Z35029
Z35038
Z40081
Z40059/Z40069
Z40075
Z40032
Z40054
Z40083
Z43016/Z43014
Z46009
CD050396/Z49399
Z49460
Z50075
Z55300
Z60040/Z60041
Z686007

Shared Product
Z69007
Z69005
CD0695025/Z70027
Z70078/Z70069/Z70017
Z80008/Z80022
Z90019
Z101051
Z101029/Z101039
Z101035/Z101046
Z102502/Z102503
Z121002
Z123007
Z133001
Z156004