

# ZHUNYI PRODUCT LIST --20260319

No.	Display Size (inch)	Shape	Display Resolution	View Direction	Active Area (mm)	LCM Outline Dimension (mm)	Thickness (mm)	Interface	Operating Temperature	Storage Temperature	Remarks	Remarks	Shared Product
1	0.71	round	160*160	IPS	18.00*18.00	20.12*22.30	1.90	SPI/MCU/RGB	-20°C ~ 70°C	-30°C ~ 80°C	-		Z07101
2	1.3"	square	240*240	IPS	23.40*23.40	26.17*29.22	1.50	SPI/MCU/RGB	-20°C ~ 70°C	-30°C ~ 80°C	-		Z13012/Z13009
3	1.28"/1.3"	round	240*240	IPS	32.40*32.40	35.60*37.74	1.60	SPI/MCU	-20°C ~ 70°C	-30°C ~ 80°C	-		Z13008
4	1.54"	square	240*240	IPS	27.72*27.72	31.52*33.72	1.90	MCU/SPI/RGB	-20°C ~ 70°C	-30°C ~ 80°C	-		Z15002/Z15013
5	1.6"	round	400*400	IPS	39.84*39.84	42.14*44.34	1.94	QSPI/RGB	-20°C ~ 70°C	-30°C ~ 80°C	-		Z16004/Z16007
6	2.0"	rectangle 3:4	240*320	IPS	30.60*40.80	34.60*47.80	2.00	MCU/SPI/RGB	-20°C ~ 70°C	-30°C ~ 80°C	-		Z20011
7	2.0"	rectangle 1:3	170*320	IPS	22.70*42.72	25.80*49.72	1.58	MCU/SPI	-20°C ~ 70°C	-30°C ~ 80°C	-		Z20016
8	2.1"	round	480*480/360*360	IPS	53.28*53.28	56.18*59.71	2.26	MCU/RGB/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	-		Z21011/Z21009
9	2.4"	rectangle 3:4	240*320	TN/IPS	36.72*48.96	40.52*57.00	2.39	MCU/SPI/MIPI/RGB	-30°C ~ 80°C	-40°C ~ 85°C	-		Z24009/Z24017/Z24023
10	2.7"/2.73"	square	320*320	IPS	48.96*48.96	53.54*58.74	2.54	MCU/RGB/SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	-		Z27002
11	2.8"	rectangle 3:4	240*320	IPS	43.20*57.60	50.00*69.20	2.30	MCU/SPI	-20°C ~ 70°C	-30°C ~ 80°C	-		Z28017
12	2.76"/2.8"	round	480*480	IPS	70.13*70.13	73.03*76.48	2.45	MCU/RGB/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	-		Z28019
13	2.83"incell	rectangle 9:18	400*800	IPS	32.10*64.20	34.30*69.40	2.12	RGB/MIPI	-30°C ~ 80°C	-40°C ~ 90°C	玻璃私模	highly recommended	Z28028
14	2.83"incell	rectangle 4:3	480*360	IPS	57.08*42.81	60.28*49.22	2.60	RGB/MIPI	-30°C ~ 80°C	-40°C ~ 90°C	玻璃私模	highly recommended	Z28036
15	3.0"	rectangle 9:16	480*854	IPS	37.44*66.61	42.70*74.70	2.50	MCU/RGB/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	玻璃私模	highly recommended	Z30010/Z30032/Z30054
16	3.4"	square	480*480	IPS	60.48*60.48	65.72*69.64	2.45	MCU/RGB/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	-		Z34011/Z34013
17	3.4"	round	800*800	IPS	87.60*87.60	94.90*96.95	2.80	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	-		Z34009
18	3.4"incell	rectangle 9:16	540*960	IPS	41.96*74.59	44.16*79.84	2.12	MIPI	-30°C ~ 80°C	-40°C ~ 90°C	玻璃私模	highly recommended	Z34023
19	3.5"	rectangle 3:4	320*480	IPS	48.96*73.44	53.76*82.39	2.30	MCU/RGB/MIPI/SPI	-30°C ~ 85°C	-30°C ~ 85°C	-		Z35037
20	3.54"	rectangle 3:4	640*960	IPS	49.92*74.88	54.22*83.58	2.30	MIPI	-30°C ~ 70°C	-30°C ~ 80°C	-		Z35049
21	3.7"	Bar	240*960	IPS	22.86*91.44	25.30*98.89	1.60	MCU/RGB/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	-		Z37003
22	3.95"	square	480*480	IPS	71.86*70.18	74.66*76.54	2.15	MCU/RGB/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	-		Z40069
23	3.95"	square	720*720	IPS	71.93*71.93	74.83*78.98	2.15	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	-		Z40066
24	3.97"	rectangle 3:4	480*800	IPS	51.84*86.40	55.44*96.15	1.71	MCU/RGB/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	-	highly recommended	Z40113
25	3.98"	rectangle 3:4	320*480	IPS	55.68*83.52	60.00*92.00	2.35	MCU/RGB/MIPI/SPI	-20°C ~ 70°C	-30°C ~ 80°C	-		Z40091-A-ZC2
26	4.1"incell	Bar	480*1080	IPS	42.00*94.50	44.10*99.45	2.06	MIPI	-20°C ~ 80°C	-30°C ~ 80°C	玻璃私模	highly recommended	Z40107
27	4.3"	rectangle 16:9	480*272	IPS	95.04*53.86	105.40*67.10	2.75	RGB/SPI	-20°C ~ 70°C	-30°C ~ 80°C	-		Z43016/Z43014
28	4.3"incell	rectangle 3:4	480*800	IPS	56.16*93.60	59.16*99.95	2.50	RGB/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	-		Z43049
29	4.6"	Bar	320*960	IPS	36.708*110.304	41.568*118.80	2.50	MCU/RGB/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	-		Z46012
30	5.0"incell	rectangle 9:16	480*854	IPS	61.78*109.91	66.40*120.05	2.20	MIPI/RGB	-20°C ~ 70°C	-30°C ~ 80°C	-		Z49466
31	5.0"	rectangle 9:16	720*1280	IPS	61.24*108.86	63.50*117.50/64.40*120.05	2.40/2.63	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	-	highly recommended	Z49460
32	5.0"incell	square	720*720	IPS	91.37*91.37	93.57*96.67	2.15	MIPI	-30°C ~ 85°C	-40°C ~ 90°C	玻璃私模	highly recommended	Z50004+HDMI/Z50006ZC/Z50005单屏
33	5.5"	rectangle 9:16	720*1280	IPS	67.65*120.27	69.85*127.10	1.80	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	-		Z55302
34	6.0"	rectangle 9:18	480*960	IPS	68.04*136.08	70.24*142.73	2.05	MIPI/RGB	-20°C ~ 70°C	-30°C ~ 80°C	-	highly recommended	Z60053
35	6.0"	rectangle 9:18	720*1480	IPS	66.74*137.20	70.50*145.20	2.08	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	-	highly recommended	Z60040/Z60041ZC+HDMI
36	6.0"incell	waterdrop screen	720*1560	IPS	64.80*140.40	67.00*146.30	2.16	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	-		Z60045
37	6.2"incell	rectangle 4:5	720*900	IPS	97.70*122.16	99.90*128.12	2.10	MIPI	-30°C ~ 80°C	-40°C ~ 90°C	玻璃私模	highly recommended	Z62002
38	6.5"incell	rectangle 9:18	540*1170	IPS	68.69*150.35	70.89*155.40	2.28	MIPI	-10°C ~ 60°C	-20°C ~ 70°C	-	highly recommended	Z65001
39	6.75"/6.86"	Bar	480*1280	IPS	60.19*160.51	65.78*171.75	2.60	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	-		Z686013+HDMI
40	6.75"/6.9"	rectangle 9:18	720*1440	IPS	78.02*156.04	81.71*163.34	2.35	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	-		Z69007
41	6.9"	Bar	280*1424	IPS	33.60*170.88	38.20*181.47	3.45	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	-		Z69005

# ZHUNYI PRODUCT LIST --20260319

No.	Display Size (inch)	Shape	Display Resolution	View Direction	Active Area (mm)	LCM Outline Dimension (mm)	Thickness (mm)	Interface	Operating Temperature	Storage Temperature	Remarks	Remarks	Shared Product
42	6.95"incell	rectangle 9:16	600*1024	IPS	89.28*152.37	95.00*163.20	2.50	MIPI	-10°C ~ 50°C	-20°C ~ 60°C	-		Z70131/Z70132
43	7.0"	rectangle 16:9	1024*600	IPS	154.21*85.92	163.70*96.90	2.55	LVDS/RGB/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	-		Z70134
44	8.0"incell	rectangle 9:16	800*1280	IPS	107.64*172.22	114.60*184.10	2.65	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	-		Z80022
45	8.9"/9.0"	rectangle 9:16	800*1280	IPS	119.28*190.85	125.48*202.90	2.60	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	玻璃私模	highly recommended	Z90019
46	10.1"	rectangle 16:9	1024*600	IPS	222.72*125.28	235.10*143.20	4.30	LVDS	-20°C ~ 70°C	-30°C ~ 80°C	-		Z101051
47	10.1"incell	rectangle 9:16	800*1280	IPS	135.36*216.58	139.56*226.50	2.40	MIPI	-20°C ~ 60°C	-30°C ~ 70°C	-		Z101065/Z101074 (要换背光型号会变)
48	10.1"incell	rectangle 9:16	1200*1920	IPS	135.36*216.58	143.06*228.56	2.40	MIPI					外挂Z101073的FOG+Z101064-A-X1背光
49	10.1"	rectangle 16:9	1280*800	IPS	216.96*135.60	224.02*147.76	2.60	LVDS	-20°C ~ 70°C	-30°C ~ 80°C	-		Z101035/Z101046
50	10.1"	rectangle 16:9	1920*1200	IPS	216.81*135.50	229.46*149.10	4.65	LVDS双8	-20°C ~ 70°C	-30°C ~ 80°C			Z101059
51	12.1"	rectangle 16:9	1280*800	IPS	261.12*163.20	275.85*179.15	5.60	LVDS	-20°C ~ 70°C	-30°C ~ 80°C	-		Z121007
52	12.3"	rectangle 16:9	1920*720	IPS	292.03*109.51	305.34*122.41	2.96	MIPI	-20°C ~ 70°C	-30°C ~ 80°C			Z123008MIPI/Z123010 LVDS
53	13.3"	rectangle 16:9	1920*1080	IPS	293.76*165.24	300.32*177.42	2.60	EDP/LVDS=直排/背折均OK	0°C ~ 50°C	-20°C ~ 60°C			Z133001
54	15.6"	rectangle 16:9	1920*1080	IPS	344.16*193.59	350.66*214.79	2.80	EDP=直排/背折均OK	0°C ~ 50°C	-20°C ~ 60°C	-		Z156004
55	6.67inch	rectangle 16:9	1080*2400	LTPS OLED	69.552*154.56	164.81*71.352	0.338	MIPI					Z67005
56	6.78inch	rectangle 16:9	2780*1264	LTPS OLED	71.2896*156.792	166.440*73.0896	0.341	MIPI					Z678001